

PRODUCT INFORMATION



Automotive Chemicals - Car Care - Lubricating

Version: **CC12/002**

Valvoline™ Silicone Spray

Silicone Spray is a light duty lubricant that lubricates, waterproofs and protects, leaving no sticky residue.

Silicone Spray is a powerful aerosol assisted lubricant with effective anti-corrosive properties. The product lubricates and protects objects in and around the house against rust and corrosion and keeps them movable.

Applications

Silicone Spray gives a non-sticky lubricating film to metal parts, plastics, wood and rubber.

Lubricates and preserves objects in the garage and in and around the house. For use on door hinges, rubber mountings, drawers, windows and sliding doors.

Can be used on bolts and nuts in cars, industrial, and household equipment. All types of hinges and locks, household rails and tools.

Also preserves and prevents sticking of rubber car seals.

Easy to use:

Hold can upright about 15-20 cm from surface to be treated and spray. After spraying, allow to dry.

For further information on how to use Silicone Spray, please scan the Quick Response code (QR code) to view our instructional video.



Features & Benefits

Superior multi-purpose performance

Silicone Spray is the modern solution to many problems. Silicone Spray gives a non-sticky lubricating film to metal parts, plastics, wood and rubber parts. The product prevents squeaking noises of small garden equipment, car doors, and two-wheelers. Effectively cleans the surface of all types of materials.

Deposit control

After use of household equipment and garden tools use Silicone Spray to lubricate and protect.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineurope.com

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Silicone Spray	
Appearance	Grease in aerosol
Colour	White
Propellant	Carbondioxide
Odor	Typical
Application temperature	0-35°C.
Specific Gravity @ 20°C.	0,630
Storage	Cool & dry

This information only applies to products manufactured in the following location(s): Europe

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://msds.valvoline.com>

Protect the environment

Take used chemicals to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces – CC12/001

™ Trademark of Valvoline, registered in various countries © 2016

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.