

Automotive Chemicals - Car Care - Lubricating

Version: CC14/003

Valvoline™ White Grease

White Grease is a high quality water and heat resistant lubricant for the long term protection of bolts, sliding doors, chains, hinges, and other moving or sliding parts.

With a non-hardening, non-dripping and non-staining formula, White Grease penetrates tiny crevices, forming a lubricating grease that stays exactly where it's sprayed.

Applications

This grease can be used on cars, garage doors, household, garden and industrial equipment.

Suitable for the protection of bolts, sliding doors, chains, hinges, and other moving or sliding parts.

Suitable for the lubrication of equipment working in damp conditions.

Easy to use:

Spray the product to the metal surface of the object. The best result will be achieved on a clean surface. After drying, a fine layer of white grease stays behind. Aerosols are flammable; do not spray onto hot objects.

For further information on how to use White Grease, please scan the Quick Response code (QR code) to view our instructional video.



Features & Benefits

Superior performance

White Grease is a high quality water and heat resistant lubricant for the long term protection of bolts, sliding doors, chains, hinges, and other moving or sliding parts.

Deposit control

Suitable for all metal-to-metal applications. Fights rust and corrosion. Dirt deposits can be wiped off easily.

Long term protection

This multi-use non-drip grease has special anti-wear additives and it retains its lubricity over a long period. Water and heat resistant for long term protection.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineurope.com

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

White Grease	
Appearance	Clear greasy liquid
Colour	White
Propellant	Carbon dioxide
Odor	Typical
Application temperature	0-+35°C.
Specific Gravity @ 20°C.	0,768
Storage	Cool & dry

This information only applies to products manufactured in the following location(s): Europe

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://msds.valvoline.com>

Protect the environment

Take used chemicals to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces – CC14/002

™ Trademark of Valvoline, registered in various countries © 2016

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.